

# AC 700

Cummins  
Mecc Alte  
D+ &



ISO8528

GC ; ) &

SZUTEST

GC - \$\$\$



2000/14/EC

&\$\$\$#( #

z) \$ z' z' D:

	"	"	"	"	Amp
400/230	700,00	560,00	638,00	510,00	920,00

## Standard Specifications

### ALTERNATOR

### TRANSFER SWITCH

# AC 700

Cummins  
Mecc Alte  
D+' &'

Manufacturer		Cummins		
Model		VTA 28 G5		
		%\$\$' "# "		
		*%&' "		
		Q &\$< DQ		
	L	28,00		
	"	140 x 152		
		13,1:1		
	fl # ı	"# "	1500	
	fl ı	L	83,00	
		L	200,00	
AbsorbedAirDischargeReSourceKey.Text	' # "	53,00		
	' # "	850		
fl ' # ı	' # "	123,00		
	° C	507		
		24 V d.c.		
	Load	%\$\$ı	'+)ı	)\$ı
	# "	140,00	104,00	73,00

		Mecc Alte		
		ECO 40-2L		
	Hz	50		
	"	680		
7cg'		0,80		
		3		
	fl ı	400/230		
	A	981		
Temperatur		H		

		fl ı		fl ı	
	"	"	"	"	L
AC 700	5590	4000	1350	2180	680
		fl ı		fl ı	
	"	"	"	"	L
AK 85	7030	5800	1610	2550	1100





# AC 700

Cummins  
Mecc Alte  
D+ &''

5? ,) !'



- 1
- 2
- 3
- 4
- 5
- 6
- 7
- 8
- 9
- 10

fl \$\$\$! '%&\$\$' Ł

'&\$\$\$#%(/# "

	"	1610
fl "Ł	"	5800
fl "Ł	"	2550
		1100